

TeSys D contactor - 3P(3 NO) - AC-3 - <= 440 V 12 A - 48 V DC coil

Local distributor code: 381802095

1802095 LC1D12ED

EAN Code: 3389110353891

Main

Range of product	TeSys Deca
Product or component type	Contactor
Device short name	LC1D
Contactor application	Motor control Resistive load
Utilisation category	AC-1 AC-4 AC-3 AC-3e
Poles description	3P
[Ue] rated operational voltage	Power circuit: <= 690 V AC 25400 Hz Power circuit: <= 300 V DC
[le] rated operational current	25 A (at <60 °C) at <= 440 V AC AC-1 for power circuit 12 A (at <60 °C) at <= 440 V AC AC-3 for power circuit 12 A (at <60 °C) at <= 440 V AC AC-3e for power circuit
[Uc] control circuit voltage	48 V DC

Complementary

Motor power kW	3 kW at 220230 V AC 50/60 Hz (AC-3) 5.5 kW at 380400 V AC 50/60 Hz (AC-3) 5.5 kW at 415440 V AC 50/60 Hz (AC-3) 7.5 kW at 500 V AC 50/60 Hz (AC-3) 7.5 kW at 660690 V AC 50/60 Hz (AC-3) 3.7 kW at 400 V AC 50/60 Hz (AC-4) 3 kW at 220230 V AC 50/60 Hz (AC-3e) 5.5 kW at 380400 V AC 50/60 Hz (AC-3e) 5.5 kW at 415440 V AC 50/60 Hz (AC-3e) 7.5 kW at 500 V AC 50/60 Hz (AC-3e) 7.5 kW at 660690 V AC 50/60 Hz (AC-3e)
Motor power hp	0.5 hp at 115 V AC 50/60 Hz for 1 phase motors 2 hp at 230/240 V AC 50/60 Hz for 1 phase motors 3 hp at 200/208 V AC 50/60 Hz for 3 phases motors 3 hp at 230/240 V AC 50/60 Hz for 3 phases motors 7.5 hp at 460/480 V AC 50/60 Hz for 3 phases motors 10 hp at 575/600 V AC 50/60 Hz for 3 phases motors
Compatibility code	LC1D
Pole contact composition	3 NO
Protective cover	With
[lth] conventional free air thermal current	25 A (at 60 °C) for power circuit 10 A (at 60 °C) for signalling circuit
Irms rated making capacity	250 A at 440 V for power circuit conforming to IEC 60947 140 A AC for signalling circuit conforming to IEC 60947-5-1 250 A DC for signalling circuit conforming to IEC 60947-5-1
Rated breaking capacity	250 A at 440 V for power circuit conforming to IEC 60947

13 Aug 2025 Life Is On Schneider



@famco_group

(Tel:01- + A 0 0 0 0 + 9

☐ Fax:∘۲1 - ۴۴99۴۶۴



[lcw] rated short-time withstand current	105 A 40 °C - 10 s for power circuit 210 A 40 °C - 1 s for power circuit 30 A 40 °C - 10 min for power circuit 61 A 40 °C - 1 min for power circuit 100 A - 1 s for signalling circuit 120 A - 500 ms for signalling circuit 140 A - 100 ms for signalling circuit	
Associated fuse rating	10 A gG for signalling circuit conforming to IEC 60947-5-1 40 A gG at <= 690 V coordination type 1 for power circuit 25 A gG at <= 690 V coordination type 2 for power circuit	
Average impedance	2.5 mOhm - Ith 25 A 50 Hz for power circuit	
Power dissipation per pole	0.36 W AC-3 1.56 W AC-1 0.36 W AC-3e	
[Ui] rated insulation voltage	Power circuit: 690 V conforming to IEC 60947-4-1 Power circuit: 600 V CSA certified Power circuit: 600 V UL certified Signalling circuit: 690 V conforming to IEC 60947-1 Signalling circuit: 600 V CSA certified Signalling circuit: 600 V UL certified	
Overvoltage category III		
Pollution degree	3	
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947	
Safety reliability level	B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1	
Mechanical durability	30 Mcycles	
Electrical durability	2 Mcycles 12 A AC-3 at Ue <= 440 V 0.8 Mcycles 25 A AC-1 at Ue <= 440 V 2 Mcycles 12 A AC-3e at Ue <= 440 V	
Control circuit type	DC standard	
Coil technology	With integral suppression device	
Control circuit voltage limits	0.10.25 Uc (-4070 °C):drop-out DC 0.71.25 Uc (-4060 °C):operational DC 11.25 Uc (6070 °C):operational DC	
Inrush power in W	5.4 W (at 20 °C)	
Hold-in power consumption in W	5.4 W at 20 °C	
Operating time	63 ±15 % ms closing 20 ±20 % ms opening	
Time constant	28 ms	
Maximum operating rate	3600 cyc/h at 60 °C	

@ @famco_group



Connections - terminals	Power circuit: screw clamp terminals 1 14 mm² - cable stiffness: flexible without cable end		
	Power circuit: screw clamp terminals 2 14 mm² - cable stiffness: flexible without		
	cable end Power circuit: screw clamp terminals 1 14 mm² - cable stiffness: flexible with cable		
	end Power circuit: screw clamp terminals 2 12.5 mm² - cable stiffness: flexible with		
	cable end Power circuit: screw clamp terminals 1 14 mm² - cable stiffness: solid without cable		
	end Power circuit: screw clamp terminals 2 14 mm² - cable stiffness: solid without cable		
	end		
	Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: flexible without cable end		
	Control circuit: screw clamp terminals 2 14 mm ² - cable stiffness: flexible without cable end		
	Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: flexible with cable end		
	Control circuit: screw clamp terminals 2 12.5 mm² - cable stiffness: flexible with cable end		
	Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: solid without		
	cable end Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: solid without		
	cable end		
Tightening torque	Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2		
	Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat \varnothing 6 mm		
	Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2 Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver pozidriv No 2		
	Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver pozidriv No 2		
Auxiliary contact composition	1 NO + 1 NC		
Auxiliary contacts type	type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1 type mirror contact 1 NC conforming to IEC 60947-4-1		
Signalling circuit frequency	25400 Hz		
Minimum switching voltage	17 V for signalling circuit		
Minimum switching current	5 mA for signalling circuit		
Insulation resistance	> 10 MOhm for signalling circuit		
Non-overlap time	1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact		
Mounting support	Rail		
	Plate		
Environment			
Standards	CSA C22.2 No 14		
	EN 60947-4-1 EN 60947-5-1		
	IEC 60947-4-1		
	IEC 60947-5-1		
	UL 60947-4-1		
	IEC 60335-1:Clause 30.2 IEC 60335-2-40:Annex JJ		
	UL 60335-2-40:Annex JJ		
	CSA C22.2 No 60947-4-1		
Product certifications	UL		
	CCC CSA		
	Marine		
	UKCA		
	EAC		
	OD 0-1		

13 Aug 2025 Life Is On Schneider 3

conforming to IACS E10 exposure to damp heat

conforming to IEC 60947-1 Annex Q category D exposure to damp heat

IP20 front face conforming to IEC 60529

TH conforming to IEC 60068-2-30

CB Scheme



IP degree of protection

Protective treatment

Climatic withstand





Permissible ambient air temperature around the device	-4060 °C 6070 °C with derating	
Operating altitude	03000 m	
Fire resistance	850 °C conforming to IEC 60695-2-1	
Flame retardance	V1 conforming to UL 94	
Mechanical robustness	Vibrations contactor open (2 Gn, 5300 Hz) Vibrations contactor closed (4 Gn, 5300 Hz) Shocks contactor open (10 Gn for 11 ms) Shocks contactor closed (15 Gn for 11 ms)	
Height	77 mm	
Width	45 mm	
Depth	95 mm	
Net weight	0.485 kg	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.000 cm
Package 1 Width	9.200 cm
Package 1 Length	11.200 cm
Package 1 Weight	519.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	15
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	8.084 kg
Unit Type of Package 3	P06
Number of Units in Package 3	120
Package 3 Height	45.000 cm
Package 3 Width	60.000 cm
Package 3 Length	80.000 cm
Package 3 Weight	74.500 kg

Logistical informations


Country of origin FR

Contractual warranty

Warranty 18 months

4 Life Is On Schneider 13 Aug 2025









Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∅ Environmental footprint	
Total lifecycle Carbon footprint	37
Environmental Disclosure	Product Environmental Profile


Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant with Exemptions
SCIP Number	50ae7612-fd2e-41e4-a369-50d0dea6e592
REACh Regulation	REACh Declaration
PVC free	Yes

Use Again

○ Repack and remanufacture	
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

13 Aug 2025 Life Is On Schneider 5




LC1D12ED



Dimensions Drawings

Dimensions



(1) Minimum electrical clearance

LC1		D09D18	D093D123	D099D129
b		77	99	80
	without cover or add-on blocks	93	93	93
С	with cover, without add-on blocks	95	95	95
с1	with LAD N or C (2 or 4 contacts)	126	126	126
c2	with LA6 DK10	138	138	138
-2	with LAD T, R, S	146	146	146
c3	with LAD T, R, S and sealing cover	150	150	150

LC1D12ED



Connections and Schema

Wiring



13 Aug 2025 Life Is On Schneider

Tel:∘۲1- ۴ Λ ∘ ∘ ∘ ∘ ۴ 9

LC1D12ED



Image of product / Alternate images

Alternative

Life Is On Schneider 13 Aug 2025







13 Aug 2025

Life Is On Schneider





Life Is On Schneider 13 Aug 2025


10


LC1D12ED



Technical Illustration

Assembly's dimensions





13 Aug 2025 Life Is On Schneider 11