



Contactor, TeSys Deca, 3P(3NO), AC-3/3e, <=440V, 32A, 220V AC 50/60Hz coil, screw clamp terminals

LC1D32M7

Main

Range of product	TeSys Deca	
Product or component type	Contactor	
Device short name	LC1D	
Contactor application	Resistive load Motor control	
Utilisation category	AC-4 AC-1 AC-3 AC-3e	
Poles description	3P	
[Ue] rated operational voltage	Power circuit: <= 690 V AC 25400 Hz Power circuit: <= 300 V DC	
[le] rated operational current	32 A (at <60 °C) at <= 440 V AC AC-3 for power circuit 50 A (at <60 °C) at <= 440 V AC AC-1 for power circuit 32 A (at <60 °C) at <= 440 V AC AC-3e for power circuit	
[Uc] control circuit voltage	220 V AC 50/60 Hz	

Complementary


Motor power kW	7.5 kW at 220230 V AC 50/60 Hz (AC-3) 15 kW at 380400 V AC 50/60 Hz (AC-3) 15 kW at 415440 V AC 50/60 Hz (AC-3) 18.5 kW at 500 V AC 50/60 Hz (AC-3) 18.5 kW at 660690 V AC 50/60 Hz (AC-3) 7.5 kW at 400 V AC 50/60 Hz (AC-4) 7.5 kW at 220230 V AC 50/60 Hz (AC-3e) 15 kW at 380400 V AC 50/60 Hz (AC-3e) 15 kW at 415440 V AC 50/60 Hz (AC-3e) 18.5 kW at 500 V AC 50/60 Hz (AC-3e) 18.5 kW at 660690 V AC 50/60 Hz (AC-3e)
Motor power hp	2 hp at 115 V AC 50/60 Hz for 1 phase motors 5 hp at 230/240 V AC 50/60 Hz for 1 phase motors 10 hp at 200/208 V AC 50/60 Hz for 3 phases motors 10 hp at 230/240 V AC 50/60 Hz for 3 phases motors 20 hp at 460/480 V AC 50/60 Hz for 3 phases motors 25 hp at 575/600 V AC 50/60 Hz for 3 phases motors
Compatibility code	LC1D
Pole contact composition	3 NO
Protective cover	With
[Ith] conventional free air thermal current	10 A (at 60 °C) for signalling circuit 50 A (at 60 °C) for power circuit
Irms rated making capacity	140 A AC for signalling circuit conforming to IEC 60947-5-1 250 A DC for signalling circuit conforming to IEC 60947-5-1 550 A at 440 V for power circuit conforming to IEC 60947
Rated breaking capacity	550 A at 440 V for power circuit conforming to IEC 60947

Sep 30, 2025 AD

Life Is On Schneider



E-mail: info@famcocorp.com @famco_group





[Icw] rated short-time withstand	260 A 40 °C - 10 s for power circuit	
current	430 A 40 °C - 1 s for power circuit	
	60 A 40 °C - 10 min for power circuit	
	138 A 40 °C - 1 min for power circuit	
	100 A - 1 s for signalling circuit	
	120 A - 500 ms for signalling circuit	
	140 A - 100 ms for signalling circuit	
Associated fuse rating	10 A gG for signalling circuit conforming to IEC 60947-5-1	
	63 A gG at <= 690 V coordination type 1 for power circuit	
	63 A gG at <= 690 V coordination type 2 for power circuit	
Average impedance	2 mOhm - Ith 50 A 50 Hz for power circuit	
Power dissipation per pole	2 W AC-3	
	5 W AC-1	
	2 W AC-3e	
[Ui] rated insulation voltage	Power circuit: 690 V conforming to IEC 60947-4-1	
-	Power circuit: 600 V CSA certified	
	Power circuit: 600 V UL certified	
	Signalling circuit: 690 V conforming to IEC 60947-1	
	Signalling circuit: 600 V CSA certified	
	Signalling circuit: 600 V UL certified	
Overvoltage category	III	
Pollution degree	3	
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947	
Safety reliability level	B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1	
,	B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO	
	13849-1	
Mechanical durability	15 Mcycles	
Electrical durability	1.65 Mcycles 32 A AC-3 at Ue <= 440 V	
•	1.4 Mcycles 50 A AC-1 at Ue <= 440 V	
	1.65 Mcycles 32 A AC-3e at Ue <= 440 V	
Control circuit type	AC at 50/60 Hz standard	
Coil technology	Without built-in suppressor module	
Control circuit voltage limits	0.30.6 Uc (-4070 °C):drop-out AC 50/60 Hz	
-	0.81.1 Uc (-4060 °C):operational AC 50 Hz	
	0.851.1 Uc (-4060 °C):operational AC 60 Hz	
	11.1 Uc (6070 °C):operational AC 50/60 Hz	
Inrush power in VA	70 VA 60 Hz cos phi 0.75 (at 20 °C)	
•	70 VA 50 Hz cos phi 0.75 (at 20 °C)	
Hold-in power consumption in VA	7.5 VA 60 Hz cos phi 0.3 (at 20 °C)	
in portor consumption in VA	7.5 VA 60 Hz cos phi 0.3 (at 20 °C) 7 VA 50 Hz cos phi 0.3 (at 20 °C)	
Heat dissipation	23 W at 50/60 Hz	
Operating time	1222 ms closing	
- p	419 ms opening	
Maximum operating rate	2600 ava/b at 60 °C	
maximum operating rate	3600 cyc/h at 60 °C	

Life Is On Schneider





Connections - terminals	Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: flexible without	
	cable end	
	Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: flexible without	
	cable end	
	Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: flexible with cable end	
	Control circuit: screw clamp terminals 2 12.5 mm ² - cable stiffness: flexible with cable end	
	Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: solid without cable end	
	Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: solid without cable end	
	Power circuit: screw clamp terminals 1 2.510 mm² - cable stiffness: flexible without cable end	
	Power circuit: screw clamp terminals 2 2.510 mm² - cable stiffness: flexible without cable end	
	Power circuit: screw clamp terminals 1 110 mm ² - cable stiffness: flexible with cable end	
	Power circuit: screw clamp terminals 2 1.56 mm² - cable stiffness: flexible with cable end	
	Power circuit: screw clamp terminals 1 1.510 mm² - cable stiffness: solid without cable end	
	Power circuit: screw clamp terminals 2 2.510 mm ² - cable stiffness: solid without cable end	
Tightening torque	Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2 Power circuit: 2.5 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Power circuit: 2.5 N.m - on screw clamp terminals - with screwdriver Philips No 2 Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver pozidriv No 2	
	Power circuit: 2.5 N.m - on screw clamp terminals - with screwdriver pozidriv No 2	
Auxiliary contact composition	1 NO + 1 NC	
Auxiliary contacts type	type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1 type mirror contact 1 NC conforming to IEC 60947-4-1	
Signalling circuit frequency	25400 Hz	
Minimum switching voltage	17 V for signalling circuit	
Minimum switching current	5 mA for signalling circuit	
Insulation resistance	> 10 MOhm for signalling circuit	
Non-overlap time	1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact	
Mounting support	Plate Rail	

Environment

Standards	CSA C22.2 No 14 EN 60947-4-1	
	EN 60947-5-1	
	IEC 60947-4-1	
	IEC 60947-5-1	
	UL 60947-4-1	
	IEC 60335-1:Clause 30.2	
	IEC 60335-2-40:Annex JJ	
	UL 60335-2-40:Annex JJ	
	CSA C22.2 No 60947-4-1	
	OOA OZZ.Z NO 00047-4-1	
Product certifications	UL	
	CCC	
	CSA	
	Marine	
	UKCA	
	EAC	
	CB Scheme	
IP degree of protection	IP20 front face conforming to IEC 60529	
Protective treatment	TH conforming to IEC 60068-2-30	
Climatic withstand	conforming to IACS E10 exposure to damp heat conforming to IEC 60947-1 Annex Q category D exposure to damp heat	
	comming to 120 coom of acting the committee and	

Sep 30, 2025 AD Life Is On Schneider

3







Permissible ambient air temperature around the device	-4060 °C 6070 °C with derating	
Operating altitude	03000 m	
Fire resistance	850 °C conforming to IEC 60695-2-1	
Flame retardance	V1 conforming to UL 94	
Mechanical robustness	Vibrations contactor open (2 Gn, 5300 Hz) Vibrations contactor closed (4 Gn, 5300 Hz) Shocks contactor closed (15 Gn for 11 ms) Shocks contactor open (8 Gn for 11 ms)	
Height	85 mm	
Width	45 mm	
Depth	92 mm	
Net weight	0.375 kg	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.000 cm
Package 1 Width	9.200 cm
Package 1 Length	11.200 cm
Package 1 Weight	412.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	20
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	8.502 kg
Unit Type of Package 3	P06
Number of Units in Package 3	160
Package 3 Height	45.000 cm
Package 3 Width	60.000 cm
Package 3 Length	80.000 cm
Package 3 Weight	76.016 kg


Contractual warranty

Warranty 18 months




Sep 30, 2025 AD













Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability

∇ Environmental footprint	
Total lifecycle Carbon footprint	147
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration
PVC free	Yes

Use Again

○ Repack and remanufacture		
End of life manual availability	End of Life Information	
Take-back	No	
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	

Sep 30, 2025 AD

Life Is On Schneider


5

LC1D32M7



Dimensions Drawings

Dimensions



- Including LAD 4BB (1)
- (2) Minimum electrical clearance

LC1		D25D38 (3-pole)
b	without add-on blocks	85
	with LAD 4BB	98
	with LA4 D●2	114(1)
b1	with LA4 DF, DT	123 ⁽¹⁾
	with LA4 DW, DL	130(1)
С	without cover or add-on blocks	90
	with cover, without add-on blocks	92
с1	with LAD N or C (2 or 4 contacts)	123
c2	with LA6 DK10, LAD 6K10	135
с3	with LAD T, R, S	143
	with LAD T, R, S and sealing cover	147
(1)	Including LAD 4BB.	

Life Is On Schneider

Sep 30, 2025 AD






Product datasheet

LC1D32M7



Connections and Schema

Wiring



Sep 30, 2025 AD

Life Is On Schneider

7

@ @famco_group

Product datasheet

LC1D32M7



Image of product / Alternate images

Alternative

Life Is On Schneider

Sep 30, 2025 AD

@ @famco_group







Sep 30, 2025 AD Life Is On Schneider

ç





Life Is On Schneider

Sep 30, 2025 AD


Product datasheet

LC1D32M7



Technical Illustration

Assembly's dimensions



Sep 30, 2025 AD

Life Is On Schneider

1