



Complete Product Range



Rotary Vane Oil-Flooded Vacuum Pumps



- Vacuum to 29.9 in. Hg (0.4 Torr)
- Quiet
- Highly efficient
- Compact
- Direct drive
- Semi-synthetic oil standard
- Gas ballast optional
- Cool running
- Multi-stage oil separation system—99.9+% efficient

MODEL	CFM Open Flow	Ultimate Pressure (Torr/In. HgV*)	HP/kW	Wt. (lbs.)
U 3.6 SA	4.4	2.3/29.83	0.4/0.3	31
U 4.20	12.4	1.5/29.9	0.9/0.7	44
U 4.40	28.2	0.5/29.91	2.4/1.8	84
U 4.70 SA	44	2.3/29.83	3/2.2	119
U 4.70 F	44	0.4/29.91	3/2.2	119
U 4.100 SA	69	2.3/29.83	5/3.6	170
U 4.100 F	69	0.4/29.91	5/3.6	170
U 4.165 SA	112	2.3/29.83	5/3.6	284
U 4.165 F	112	0.4/29.91	5/3.6	284
U 4.190 SA	131	2.3/29.83	7.5/5.5	359
U 4.190 F	131	0.4/29.91	7.5/5.5	359
U 4.250 SA	162	2.3/29.83	10/7.5	393
U 4.250 F	162	0.4/29.91	10/7.5	393
U 4.400 SA	299	2.3/29.83	15/11	882
U 4.400 F	299	0.4/29.91	15/11	882
U 4.630 SA	431	2.3/29.83	25/18.7	1157
U 4.630 F	431	0.4/29.91	25/18.7	1157

* Based on standard barometric pressure of 29.92 in. Hg

12