

UT320A and UT320D are single and dual channel contact type thermometers respectively. These highly accurate thermometers have a wide temperature range. UT320D can also calculate the temperature difference of its two channels. UT320 can be used with any K or J temperature probe.



UT320D



Specifications	Range	UT320A	UT320D
Certificates	CE, UKCA		
Temperature measurement (K)	-50°C~1300°C	±(0.5%+1)	±(0.5%+1)
Temperature measurement (J)	-50°C~1200°C	±(0.5%+1)	±(0.5%+1)
Display mode		Single	Dual
Difference measurement (T1-T2)			√
Operating temperature	0°C~40°C		
Operating humidity	≤80%RH		

Features	
Auto power off	MAX/MIN/AVG
Low battery indication	Mode selection (K/J)
Data hold	Backlight
°C/°F selection	1m drop proof

Characteristics	
Standard accessories	K-type temperature probe, batteries, English manual
Power	1.5V battery (R03) x 3
Display	37.4 x 36.4mm
Product size	120 x 53 x 28mm
Product net weight	60g
Standard individual packing	Gift box
Standard quantity per carton	20pcs
Standard carton measurement	332 x 225 x 200mm
Standard carton gross weight	3.4kg

UT325 contact type thermometer provide fast, accurate, and precise temperature measurement with thermocouple temperature probes. Users can select single or dual input, record, and analyze data through PC software. UT325 can be used with a variety of temperature probes, satisfying multiple applications.



UT325

Specifications	Range	Accuracy
Certificates	CE, UKCA	
Single or dual input	Dual	
Temperature probe type	Type K	-200°C~1372°C (-328°F~2501°F)
	Type J	-210°C~1200°C (-346°F~2192°F)
	Type T	-250°C~400°C (-418°F~752°F)
	Type E	-150°C~1000°C (-238°F~1832°F)
	Type R	0°C~1767°C (32°F~3212°F)
	Type S	0°C~1767°C (32°F~3212°F)
	Type N	-200°C~1300°C (-328°F~2372°F)
Resolution	0.1°C (When value>999.9°C: 1°C)	
Data storage	100	
High/low alarm	√	
High/low signal output	√	

Features	
°C/°F/K selection	MAX/MIN/AVG mode
Data hold	USB interface
Auto power off	LCD backlight alarm
Low battery indication	Auto calibration

Characteristics	
Standard accessories	Battery, USB interface cable, K-type temperature probe, English manual
Power	USB or 9V battery (6F22)
Display	30 x 32mm
Product size	175 x 85 x 30mm
Product net weight	270g
Standard individual packing	Gift box
Standard quantity per carton	10pcs
Standard carton measurement	405 x 290 x 165mm
Standard carton gross weight	4.3kg